

FILTER SOLUTIONS

1-HIGH INDUSTRIAL CARTRIDGE FILTERS

DESIGN PARAMETERS: FLOW BASED ON 5 USGPM/10" HIGH CARTRIDGE

MATERIAL OF CONSTRUCTION: CARBON STEEL, STAINLESS STEEL AND OTHER EXOTIC MATERIALS

STAINLESS STEEL : GLASS BEAD INSIDE AND OUTSIDE

CARBON STEEL : EXTERNAL SURFACE PAINTED WITH ENAMEL

MODEL NO.	VESSEL DIA (PIPE) (INCHES)	INLET OUTLET (INCHES)	NUMBER OF ELEMENTS	HEIGHT OF ELEMENTS (INCHES)	A (INCHES)	B (INCHES)	C (INCHES)	D (INCHES)	MAX FLOW (USGPM)	WEIGHT (LBS)
3R X1H	6.625	1	3	10	7	11	15	32	15	68
6RX1H	8.625	1	6	10	8	11	15	32	30	88
10RX1H	10.75	1.5	10	10	9	11	16	34	50	118

DESIGN PARAMETERS:

DESIGN PRESSURE : 150 PSIG

DESIGN TEMPERATURE : 225° F

CARTRIDGE TYPES AVAILABLE:

STANDARD:

DOUBLE OPEN ENDED

WITH SPRING SEAL

NO POST.

OPTION :

DOUBLE OPEN END WITH
POSITIVE TIE DOWN.

O-RING # 222

O-RING #226 WITH LOCKING
TABS

