

# FILTER SOLUTIONS

## 2-HIGH INDUSTRIAL CARTRIDGE FILTERS

DESIGN PARAMETERS: FLOW BASED ON 5 USGPM/10" HIGH CARTRIDGE

MATERIAL OF CONSTRUCTION: CARBON STEEL, STAINLESS STEEL AND OTHER EXOTIC MATERIALS

STAINLESS STEEL : GLASS BEAD INSIDE AND OUTSIDE

CARBON STEEL : EXTERNAL SURFACE PAINTED WITH ENAMEL

| MODEL NO. | VESSEL DIA<br>(PIPE)<br>(INCHES) | INLET<br>OUTLET<br>(INCHES) | NUMBER<br>OF<br>ELEMENTS | HEIGHT OF<br>ELEMENTS<br>(INCHES) | A<br>(INCHES) | B<br>(INCHES) | C<br>(INCHES) | D<br>(INCHES) | MAX FLOW<br>(USGPM) | WEIGHT<br>(LBS) |
|-----------|----------------------------------|-----------------------------|--------------------------|-----------------------------------|---------------|---------------|---------------|---------------|---------------------|-----------------|
| 3R X2H    | 6.625                            | 1.5                         | 3                        | 20                                | 7             | 21            | 15            | 43            | 30                  | 76              |
| 6RX2H     | 8.625                            | 1.5                         | 6                        | 20                                | 8             | 21            | 15            | 43            | 60                  | 100             |
| 10RX2H    | 10.75                            | 2                           | 10                       | 20                                | 9             | 22            | 16            | 45            | 100                 | 135             |

DESIGN PARAMETERS:  
 DESIGN PRESSURE : 150 PSIG  
 DESIGN TEMPERATURE : 225° F

CARTRIDGE TYPES AVAILABLE:  
 STANDARD:  
 DOUBLE OPEN ENDED  
 WITH SPRING SEAL  
 NO POST.

OPTION :  
 DOUBLE OPEN END WITH  
 POSITIVE TIE DOWN.  
 O-RING # 222  
 O-RING #226 WITH LOCKING  
 TABS

