

FILTER SOLUTIONS

2-HIGH INDUSTRIAL CARTRIDGE FILTERS

DESIGN PARAMETERS: FLOW BASED ON 5 USGPM/10" HIGH CARTRIDGE

MATERIAL OF CONSTRUCTION: CARBON STEEL, STAINLESS STEEL AND OTHER EXOTIC MATERIALS

STAINLESS STEEL : GLASS BEAD INSIDE AND OUTSIDE

CARBON STEEL : EXTERNAL SURFACE PAINTED WITH ENAMEL

MODEL NO.	VESSEL DIA (PIPE) (INCHES)	INLET OUTLET (INCHES)	NUMBER OF ELEMENTS	HEIGHT OF ELEMENTS (INCHES)	A (INCHES)	B (INCHES)	C (INCHES)	D (INCHES)	MAX FLOW (USGPM)	WEIGHT (LBS)
12RX2H	12.75	2.0	12	20	11	22	19	48	120	194
18RX2H	14	3	18	20	12	22	20	49	180	257
22RX2H	16	3	22	20	12	22	20	49	220	304
28RX2H	18	3	28	20	13	22	21	51	280	380
36RX2H	20	4	36	20	14	23	22	53	360	440

DESIGN PARAMETERS:

DESIGN PRESSURE : 150 PSIG

DESIGN TEMPERATURE : 225° F

CARTRIDGE TYPES AVAILABLE:

STANDARD:

DOUBLE OPEN ENDED
WITH SPRING SEAL
NO POST.

OPTION :

DOUBLE OPEN END WITH
POSITIVE TIE DOWN.
O-RING # 222
O-RING #226 WITH LOCKING
TABS

