

FILTER SOLUTIONS

3-HIGH INDUSTRIAL CARTRIDGE FILTERS

DESIGN PARAMETERS: FLOW BASED ON 5 USGPM/10" HIGH CARTRIDGE

MATERIAL OF CONSTRUCTION: CARBON STEEL, STAINLESS STEEL AND OTHER EXOTIC MATERIALS

STAINLESS STEEL : GLASS BEAD INSIDE AND OUTSIDE

CARBON STEEL : EXTERNAL SURFACE PAINTED WITH ENAMEL

MODEL NO.	VESSEL DIA (PIPE) (INCHES)	INLET OUTLET (INCHES)	NUMBER OF ELEMENTS	HEIGHT OF ELEMENTS (INCHES)	A (INCHES)	B (INCHES)	C (INCHES)	D (INCHES)	MAX FLOW (USGPM)	WEIGHT (LBS)
3R X3H	6.625	1.5	3	30	7	31	15	53	45	84
6RX3H	8.625	2	6	30	8	32	15	53	90	112
10RX3H	10.75	3	10	30	9	32	17	56	150	153

DESIGN PARAMETERS:
 DESIGN PRESSURE : 150 PSIG
 DESIGN TEMPERATURE : 225° F

CARTRIDGE TYPES AVAILABLE:
 STANDARD:
 DOUBLE OPEN ENDED
 WITH SPRING SEAL
 NO POST.

OPTION :
 DOUBLE OPEN END WITH
 POSITIVE TIE DOWN.
 O-RING # 222
 O-RING #226 WITH LOCKING
 TABS

