

FILTER SOLUTIONS

4-HIGH INDUSTRIAL CARTRIDGE FILTERS

DESIGN PARAMETERS: FLOW BASED ON 5 USGPM/10" HIGH CARTRIDGE

MATERIAL OF CONSTRUCTION: CARBON STEEL, STAINLESS STEEL AND OTHER EXOTIC MATERIALS

STAINLESS STEEL : GLASS BEAD INSIDE AND OUTSIDE

CARBON STEEL : EXTERNAL SURFACE PAINTED WITH ENAMEL

MODEL NO.	VESSEL DIA (PIPE) (INCHES)	INLET OUTLET (INCHES)	NUMBER OF ELEMENTS	HEIGHT OF ELEMENTS (INCHES)	A (INCHES)	B (INCHES)	C (INCHES)	D (INCHES)	MAX FLOW (USGPM)	WEIGHT (LBS)
3R X4H	6.625	1.5	3	40	7	41	15	63	60	92
6RX4H	8.625	2	6	40	8	42	15	63	120	123
10RX4H	10.75	3	10	40	9	42	17	66	200	168

DESIGN PARAMETERS:

DESIGN PRESSURE : 150 PSIG

DESIGN TEMPERATURE : 225° F

CARTRIDGE TYPES AVAILABLE:

STANDARD:

DOUBLE OPEN ENDED

WITH SPRING SEAL

NO POST.

OPTION :

DOUBLE OPEN END WITH

POSITIVE TIE DOWN.

O-RING # 222

O-RING #226 WITH LOCKING TABS

