

FILTER SOLUTIONS

4-HIGH INDUSTRIAL CARTRIDGE FILTERS

DESIGN PARAMETERS: FLOW BASED ON 5 USGPM/10" HIGH CARTRIDGE

MATERIAL OF CONSTRUCTION: CARBON STEEL, STAINLESS STEEL AND OTHER EXOTIC MATERIALS

STAINLESS STEEL : GLASS BEAD INSIDE AND OUTSIDE

CARBON STEEL : EXTERNAL SURFACE PAINTED WITH ENAMEL

MODEL NO.	VESSEL DIA (PIPE) (INCHES)	INLET OUTLET (INCHES)	NUMBER OF ELEMENTS	HEIGHT OF ELEMENTS (INCHES)	A (INCHES)	B (INCHES)	C (INCHES)	D (INCHES)	MAX FLOW (USGPM)	WEIGHT (LBS)
12RX4H	12.75	3	12	40	11	42	20	69	240	237
18RX4H	14	4	18	40	12	43	20	71	360	323
22RX4H	16	4	22	40	12	43	20	71	440	374
28RX4H	18	6	28	40	13	43	22	74	560	463
36RX4H	20	6	36	40	14	43	23	75	720	521

DESIGN PARAMETERS:

DESIGN PRESSURE : 150 PSIG

DESIGN TEMPERATURE : 225° F

CARTRIDGE TYPES AVAILABLE:

STANDARD:

**DOUBLE OPEN ENDED
WITH SPRING SEAL
NO POST.**

OPTION :

**DOUBLE OPEN END WITH
POSITIVE TIE DOWN.
O-RING # 222
O-RING #226 WITH LOCKING
TABS**

