

FILTER SOLUTIONS

Carbon Steel & Stainless Steel Simplex Inline Fabricated Strainers Dimensional Data for 300# Flanged Strainers

Inlet/Outlet Size	2 "	2.5 "	3 "	4 "	6 "	8 "
Housing Dia. in Pipe Size	4 "	4 "	6 "	6 "	8 "	10 "
A	14 "	14 "	16 "	19 "	21 "	21 "
B	5.5 "	6 "	6 "	7 "	8.5 "	9.5 "
C	16.5 "	19.75 "	20 "	25 "	27.5 "	33.625 "
D	8.75 "	11.75 "	11.75 "	15.75 "	16.25 "	21.25 "
E	12 "	16 "	15 "	20 "	21 "	26 "
Basket Dia.	2 "	2 "	3.75 "	3.75 "	5.75 "	7.75 "
Basket Length	6 "	9 "	8 "	12 "	12 "	16 "
Ship'ng. Wt (Lbs)	98	102	156	179	268	422
Min. Perf. Size	1/32 "	1/32 "	1/32 "	1/32 "	1/16 "	1/16 "
Min. Basket Open Area Sq. Inches	10	15	22	38	85	151

Standard Perforation Diameter 1/8"
 CSA B51 Certified with Canadian Registration Number (CRN)
 Standard Design Pressure & Temperature 667 PSIG @ 100 Deg. F. or 635 PSIG @ 400 Deg. F.
 Special Design Pressures & Temperatures available upon request

